CATFORD 1.6Kw 12V DC HYDRAULIC POWER PACK 3.8 LITRE TANK P&T (DOUBLE ACTING)

Features:

* These DC Power Pack Units can be mounted horizontally or vertically. (DC Motor up)

* These DC Power Pack Units have been designed for double acting hydraulic cylinders on log splitters, tail gate loaders, ute tipper trays, ramps on low loaders, small cranes or for any double acting hydraulic cylinders that is used intermittently.



All our DC Power Packs are certified worldwide with the following ISO standard ISO 9001-2008 Standard

ISO 14001 & OSHAS 18001 ISO 3834-2 (welding process)

1) 1.6Kw P&T (DOUBLE ACTING) (Part Number: 1612PTDC38)

\$660 Inc GST

- 2) 1.6Kw P&T (DOUBLE ACTING) One Station with double solenoid pendant controller with 3 metre cord. (Part Number: P1612PTDC381S) \$820 Inc GST
- 3) 1.6Kw P&T (DOUBLE ACTING) Two Station with double solenoid pendant controller with 3 metre cord. (Part Number: P1612PTDC382S) \$1,120 Inc GST
- 4) 1.6Kw P&T (DOUBLE ACTING Three Station with double solenoid pendant controller with 3 metre cord. (Part Number: P1612PTDC383S) \$1,420 Inc GST

CATFORD 2.2Kw 12V DC HYDRAULIC POWER PACK 3.8 LITRE TANK P&T (DOUBLE ACTING)

Features:

* These DC Power Pack Units can be mounted horizontally or vertically. (DC Motor up)

* These DC Power Pack Units have been designed for double acting hydraulic cylinders on log splitters, tail gate loaders, ute tipper trays, ramps on low loaders, small cranes or for any double acting hydraulic cylinders that is used intermittently.

> Charles: 0418 641 566 Email: <u>sales@catford.com.au</u>



All our DC Power Packs are certified worldwide with the following ISO standard

ISO 9001-2008 Standard ISO 14001 & OSHAS 18001 ISO 3834-2 (welding process)

1) 2.2Kw P&T (DOUBLE ACTING) (Part Number: 2212PTDC38)

\$730 Inc GST

12V

- 2) 2.2Kw P&T (DOUBLE ACTING) One Station with double solenoid pendant controller with 3 metre cord. (Part Number: P2212PTDC381S) \$1010 Inc GST
- 3) 2.2Kw P&T (DOUBLE ACTING) Two Station with double solenoid pendant controller with 3 metre cord. (Part Number: P2212PTDC382S) \$1,180 Inc GST
- 4) 2.2Kw P&T (DOUBLE ACTING Three Station with double solenoid pendant controller with 3 metre cord. (Part Number: P2212PTDC383S) \$1,485 Inc GST

CATFORD 2.2Kw 12V DC HYDRAULIC POWER PACK 7.5 LITRE TANK (SINGLE ACTING) with Pendant

Part Number: (P2212SDC38)

60

All our DC Power Packs are certified worldwide with the following ISO standard

ISO 9001-2008 Standard ISO 14001 & OSHAS 18001 ISO 3834-2 (welding process)

Features:

* This DC Power Pack Units can be mounted horizontally or vertically (DC Motor up)

* This DC Power Pack Units has been designed for single acting hydraulic cylinders on tail gate loaders, ute tipper trays, ramps on low loaders, small cranes or for any double acting hydraulic cylinders that is used intermittently.

Price: \$825 Inc GST

Phone Charles: 0418 641 556 Email: sales@catford.com.au

CATFORD 3Kw 24V DC HYDRAULIC POWER PACK 3.8 LITRE TANK P&T (DOUBLE ACTING)

Features:

* These DC Power Pack Units can be mounted horizontally or vertically. (DC Motor up)

* These DC Power Pack Units have been designed for double acting hydraulic cylinders on log splitters, tail gate loaders, ute tipper trays, ramps on low loaders, small cranes or for any double acting hydraulic cylinders that is used intermittently.

> Charles: 0418 641 566 Email: <u>sales@catford.com.au</u>

worldwide with the following ISO standard ISO 9001-2008 Standard ISO 14001 & OSHAS 18001 ISO 3834-2 (welding process)

All our DC Power Packs are certified

1) 3Kw P&T (DOUBLE ACTING) (Part Number: 324PTDC38)

\$990 Inc GST

- 2) 3Kw P&T (DOUBLE ACTING) One Station with double solenoid pendant controller with 3 metre cord. (Part Number: P324PTDC381S) \$1,386 Inc GST
- 3) 3Kw P&T (DOUBLE ACTING) Two Station with double solenoid pendant controller with 3 metre cord. (Part Number: P324PTDC382S) \$1,820 Inc GST
- 4) 3Kw P&T (DOUBLE ACTING Three Station with double solenoid pendant controller with 3 metre cord. (Part Number: P324PTDC383S) \$2,180 Inc GST

Wireless Pendant Controllers

Single Station Double Acting

(12 & 24 Volt DC) Part Number : WPC1



Wireless Controller Specifications

Wireless Receiver Unit \$1400 Including GST

- 1) Sensitivity of RF-110dbm 100m
- 2) Antenna Internal type
- 3) Power Supply : 12 to 24 Volt DC
- 4) Power Consumption <12mA
- 5) Connector : Water proof SD16 connector with 5/7/9 pins
- 6) Cable Length : 4 Metres
- 7) Sensing Distance : Up to 20 Metres

Wireless Pendant Unit

NGINEERING PRODUCTS

www.catford.com.au sales@catford.com.au

1) Operating Distance : 0 to 20 Metres

- 2) Powered with Rechargeable Battery Supply
- 3) Inbuilt Ni-MH Battery, 3-6 Volt DC, 600mAH
- 4) Power ON/OFF switch option available to save the battery voltage
- 5) Battery charging through a micro USB connector


Jamestown

Phone: 0418 641 566 \$1600 Including GST

SA 5491

6) Indication of RED LED for charging & GREEN once it is charged

Two Station Double Acting (12 & 24 Volt DC) Part Number : WPC2



\$1200 Including GST

ATFORD