

# CATFORD 1.6Kw 12V DC HYDRAULIC POWER PACK 7.5 LITRE TANK (SINGLE ACTING) With Pendant

## 1.6Kw Single Acting Specifications

- \*1.6Kw DC Power Pack
- \*DC Motor : 1.6Kw 12V, 2600 RPM
- \*Single Acting with Pendant
- \*System Working Pressures : 140 Bar/2030 PSI
- \*System Oil Flow : 4.5 LPM
- \*Gear Oil Pump : PP20 (2.1cc)
- \*Ports : 3/8" BSPP
- \*Weight without oil : 17Kgs
- \*Oil Tank : 7.5Ltrs

## Features:

- \*This DC Power Pack Unit can be mounted horizontally or vertically (DC Motor up)
- \*This DC Power Pack Unit has been designed for single acting hydraulic cylinders on tail gate loaders, ute tipper trays, ramps on low loaders, small cranes or for any single acting hydraulic cylinders that is used intermittently.



Part Number : P1612SDC38

Price \$1,078 Including GST

**CATFORD**  
**ENGINEERING**  
PRODUCTS

Jamestown  
SA 5491

Phone: 0418 641 566

www.catford.com.au sales@catford.com.au

# CATFORD 1.6Kw 12V DC HYDRAULIC POWER PACK 3.8 LITRE TANK P&T (DOUBLE ACTING)

## 1.6Kw Double Acting Specifications

- \*1.6Kw DC Power Pack
- \*DC Motor : 1.6Kw 12V, 2600 RPM
- \*Double Acting with Pendant
- \*System Working Pressures : 140 Bar/2030 PSI
- \*System Oil Flow : 4.5 LPM
- \*Gear Oil Pump : PP20 (2.1cc)
- \*Ports : 3/8" BSPP
- \*Oil Tank : 3.8Ltrs

## Features:

- \* These DC Power Pack Units can be mounted horizontally or vertically. (DC Motor up)
- \* These DC Power Pack Units have been designed for double acting hydraulic cylinders on log splitters, tail gate loaders, ute tipper trays, ramps on low loaders, small cranes or for any double acting hydraulic cylinders that is used intermittently.



**Charles: 0418 641 566**

**Email: [sales@catford.com.au](mailto:sales@catford.com.au)**

- 1. 1.6Kw P&T (DOUBLE ACTING)**  
**(Part Number: 1612PTDC38) \$880 Including GST**
- 2. 1.6Kw P&T (DOUBLE ACTING) One Station** with double solenoid pendant controller with 3 metre cord.  
**(Part Number: P1612PTDC381S) \$1,100 Including GST**
- 3. 1.6Kw P&T (DOUBLE ACTING) Two Station** with double solenoid pendant controller with 3 metre cord.  
**(Part Number: P1612PTDC382S) \$1,342 Including GST**
- 4. 1.6Kw P&T (DOUBLE ACTING) Three Station** with double solenoid pendant controller with 3 metre cord.  
**(Part Number: P1612PTDC383S) \$1,705 Including GST**

# CATFORD 2.2Kw 12V DC HYDRAULIC POWER PACK 7.5 LITRE TANK (SINGLE ACTING) with Pendant

## 2.2Kw Single Acting Specifications

- \*2.2Kw DC Power Pack
- \*DC Motor : 2.2Kw 12V, 2600 RPM
- \*Single Acting with Pendant
- \*System Working Pressures : 200 Bar/2900 PSI
- \*System Oil Flow : 4.7 LPM
- \*Gear Oil Pump : PP20 (2.1cc)
- \*Ports : 3/8" BSPP
- \*Weight without oil : 20Kgs
- \*Oil Tank : 7.5Ltrs

## Features:

- \*This DC Power Pack Unit can be mounted horizontally or vertically (DC Motor up)
- \*This DC Power Pack Unit has been designed for single acting hydraulic cylinders on tail gate loaders, ute tipper trays, ramps on low loaders, small cranes or for any single acting hydraulic cylinders that is used intermittently.



**CATFORD**  
**ENGINEERING**  
PRODUCTS

Jamestown  
SA 5491

Phone: 0418 641 566

www.catford.com.au sales@catford.com.au

Part Number : P2212SDC38

**Price \$1,122 Including GST**

# CATFORD 2.2Kw 12V DC HYDRAULIC POWER PACK 3.8 LITRE TANK P&T (DOUBLE ACTING)

## 2.2Kw Double Acting Specifications

- \*2.2Kw DC Power Pack
- \*DC Motor : 2.2Kw 12V, 2600 RPM
- \*Double Acting with Pendant
- \*System Working Pressures : 200 Bar/2900 PSI
- \*System Oil Flow : 4.7 LPM
- \*Gear Oil Pump : PP20 (2.1cc)
- \*Ports : 3/8" BSPP
- \*Oil Tank : 3.8Ltrs

## Features:

- \*These DC Power Pack Units can be mounted horizontally or vertically (DC Motor up)
- \*These DC Power Pack Units have been designed for double acting hydraulic cylinders on tail gate loaders, ute tipper trays, ramps on low loaders, small cranes or for any double acting hydraulic cylinders that is used intermittently.



Charles: 0418 641 566  
Email: [sales@catford.com.au](mailto:sales@catford.com.au)



- 1) 2.2Kw P&T (DOUBLE ACTING)  
(Part Number: 2212PTDC38) \$990 Including GST
- 2) 2.2Kw P&T (DOUBLE ACTING) **One Station** with double solenoid pendant controller with 3 metre cord.  
(Part Number: P2212PTDC381S) \$1210 Including GST
- 3) 2.2Kw P&T (DOUBLE ACTING) **Two Station** with double solenoid pendant controller with 3 metre cord.  
(Part Number: P2212PTDC382S) \$1,419 Including GST
- 4) 2.2Kw P&T (DOUBLE ACTING) **Three Station** with double solenoid pendant controller with 3 metre cord.  
(Part Number: P2212PTDC383S) \$1,782 Including GST

# CATFORD 3Kw 24V DC HYDRAULIC POWER PACK 3.8 LITRE TANK P&T (DOUBLE ACTING)

## 3Kw Double Acting Specifications

- \*3Kw DC Power Pack
- \*DC Motor : 3Kw 24V, 3000 RPM
- \*Double Acting with Pendant
- \*System Working Pressures : 200 Bar/2900 PSI
- \*System Oil Flow : 6.2 LPM
- \*Gear Oil Pump : PP20 (2.1cc)
- \*Ports : 3/8" BSPP
- \*Oil Tank : 3.8Ltrs

## Features:

- \*These DC Power Pack Units can be mounted horizontally or vertically (DC Motor up)
- \*These DC Power Pack Units have been designed for double acting hydraulic cylinders on log splitters tail gate loaders, ute tipper trays, ramps on low loaders, small cranes or for any double acting hydraulic cylinders that is used intermittently.



Charles: 0418 641 566  
Email: [sales@catford.com.au](mailto:sales@catford.com.au)

- 1) 3Kw P&T (DOUBLE ACTING)  
(Part Number: 324PTDC38) \$1,298 Including GST
- 2) 3Kw P&T (DOUBLE ACTING) **One Station** with double solenoid pendant controller with 3 metre cord.  
(Part Number: P324PTDC381S) \$1,672 Including GST
- 3) 3Kw P&T (DOUBLE ACTING) **Two Station** with double solenoid pendant controller with 3 metre cord.  
(Part Number: P324PTDC382S) \$2,178 Including GST
- 4) 3Kw P&T (DOUBLE ACTING) **Three Station** with double solenoid pendant controller with 3 metre cord.  
(Part Number: P324PTDC383S) \$2,618 Including GST

# Wireless Pendant Controllers

Single Station Double Acting  
(12 & 24 Volt DC)  
Part Number : WPC1



**\$1200 Including GST**

## Wireless Controller Specifications

Wireless Receiver Unit **\$1400 Including GST**

- 1) Sensitivity of RF-110dbm 100m
- 2) Antenna Internal type
- 3) Power Supply : 12 to 24 Volt DC
- 4) Power Consumption <12mA
- 5) Connector : Water proof SD16 connector with 5/7/9 pins
- 6) Cable Length : 4 Metres
- 7) Sensing Distance : Up to 20 Metres

## Wireless Pendant Unit

- 1) Operating Distance : 0 to 20 Metres
- 2) Powered with Rechargeable Battery Supply
- 3) Inbuilt Ni-MH Battery, 3-6 Volt DC, 600mAH
- 4) Power ON/OFF switch option available to save the battery voltage
- 5) Battery charging through a micro USB connector
- 6) Indication of RED LED for charging & GREEN once it is charged

Two Station Double Acting  
(12 & 24 Volt DC)  
Part Number : WPC2



Three Station Double Acting  
(12 & 24 Volt DC)  
Part Number : WPC3



**\$1600 Including GST**

**CATFORD**  
**ENGINEERING**  
**PRODUCTS**

Jamestown  
SA 5491

Phone: 0418 641 566

www.catford.com.au sales@catford.com.au